



# CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

## CABLE TYPE : CTW-CV-AWA SINGLE CORE CU/XLPE/AWA/PVC 1.8/3 (3.6) kV

MEDIUM VOLTAGE CROSS-LINKED POLYETHYLENE INSULATED, COPPER CONDUCTOR WITH ALUMINUM WIRE ARMOUR



### CONSTRUCTION

Conductor	Compact round stranded annealed copper.
Conductor Screen	Semi-conducting cross-linked polyethylene.
Insulation	Cross-linked polyethylene. (XLPE)
Insulation Screen	Semi-conducting cross-linked polyethylene.
Metallic Shield	Annealed copper tape.
Separator Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)
Armour	Aluminum wire.
Separator Tape	Polyester and/or Spunbond tape.
Outer Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)

### APPLICATION

Preferably used for urban networks. Exposed in aerial, direct burial, conduit, open tray and underground duct installation.

### CLASSIFICATION

Maximum Conductor Temperature 90 °C (Normal Operation)  
Maximum Conductor Temperature 250 °C (Short-circuit at 5s maximum duration)

### REFERENCE

IEC 60228 & IEC 60502-1  
\*\* AC Test Voltage : 6.5 kV

### NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF) Flame retardant sheath can be supplied in accordance with IEC 60332-3.

Product code	Conductor			Thickness of insulation (mm)	Diameter over insulation (Approx.) (mm)	Diameter of armour wire (mm)	Diameter over Armour (Approx.) (mm)	Thickness of outer sheath (mm)	Overall diameter (Approx.) (mm)	Cable weight (Approx.) (kg/km)	Maximum conductor resistance at 20°C (Ω/km)	Minimum insulation resistance at 20°C (MΩ-km)	Ampacities direct burial in ground at 30°C (A)	Allowable ampacities in free air at 40°C (ambient) (A)	Standard length (m/R)
	Nominal cross-sectional area core x mm <sup>2</sup>	Minimum number of wire No./mm	Diameter (Approx.) (mm)												
K3A621010	1 x 10	6	3.72	2.0	9.0	1.25	15.90	1.8	20	540	1.83	2,700	90	100	1,000
K3A621016	1 x 16	6	4.69	2.0	10.0	1.25	16.90	1.8	21	630	1.15	2,400	115	125	1,000
K3A621025	1 x 25	6	5.90	2.0	11.5	1.6	18.80	1.8	23	800	0.727	2,100	150	165	1,000
K3A621035	1 x 35	6	6.95	2.0	12.5	1.6	19.90	1.8	24	940	0.524	1,800	180	200	1,000
K3A621050	1 x 50	6	8.33	2.0	13.5	1.6	21.20	1.8	26	1,120	0.387	1,600	210	240	1,000
K3A621070	1 x 70	12	9.73	2.0	15.5	1.6	22.70	1.8	27	1,360	0.268	1,400	260	295	1,000
K3A621095	1 x 95	15	11.45	2.0	17.0	1.6	24.40	1.9	29	1,670	0.193	1,200	310	365	1,000
K3A621120	1 x 120	18	12.95	2.0	18.5	1.6	25.90	1.9	30	1,950	0.153	1,100	350	420	1,000
K3A621150	1 x 150	18	14.27	2.0	20.0	1.6	27.30	2.0	32	2,290	0.124	1,100	395	475	1,000
K3A621185	1 x 185	30	15.98	2.0	21.5	2.0	29.80	2.0	34	2,760	0.0991	900	450	545	500
K3A621240	1 x 240	34	18.47	2.0	24.0	2.0	32.30	2.1	37	3,380	0.0754	800	520	640	500
K3A621300	1 x 300	34	20.68	2.0	26.5	2.0	34.50	2.2	40	4,040	0.0601	700	585	740	500
K3A621400	1 x 400	53	23.39	2.0	29.5	2.0	37.50	2.3	43	5,110	0.0470	700	670	850	500
K3A621500	1 x 500	53	26.67	2.2	33.5	2.5	42.50	2.5	48	6,400	0.0366	700	760	975	250
K3A621630	1 x 630	53	30.20	2.4	37.5	2.5	46.60	2.6	53	7,900	0.0283	600	860	1,130	250
K3A621800	1 x 800	53	34.00	2.6	41.5	2.5	51.10	2.8	57	9,780	0.0221	600	1,025	1,330	250
K3A6211000	1 x 1,000	53	40.00	2.8	47.5	2.5	57.80	3.0	64	12,070	0.0176	600	1,215	1,520	200

\*\* Depth of laying in ground = 1 m, Rho = 1.2 °C m/watt, Spacing of cable = 2 x cable overall diameter

R = Packing in reel



# CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

## CABLE TYPE : CTW-CV-AWA SINGLE CORE CU/XLPE/AWA/PVC 3.6/6 (7.2) kV

MEDIUM VOLTAGE CROSS-LINKED POLYETHYLENE INSULATED, COPPER CONDUCTOR WITH ALUMINUM WIRE ARMOUR



### CONSTRUCTION

Conductor	Compact round stranded annealed copper.
Conductor Screen	Semi-conducting cross-linked polyethylene.
Insulation	Cross-linked polyethylene. (XLPE)
Insulation Screen	Semi-conducting cross-linked polyethylene.
Metallic Shield	Annealed copper tape.
Separator Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)
Armour	Aluminum wire.
Separator Tape	Polyester and/or Spunbond tape.
Outer Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)

### APPLICATION

Preferably used for urban networks. Exposed in aerial, direct burial, conduit, open tray and underground duct installation.

### CLASSIFICATION

Maximum Conductor Temperature 90 °C (Normal Operation)  
Maximum Conductor Temperature 250 °C (Short-circuit at 5s maximum duration)

### REFERENCE

IEC 60228 & IEC 60502-2  
\*\* AC Test Voltage : 12.5 kV

### NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF) Flame retardant sheath can be supplied in accordance with IEC 60332-3.

Product code	Conductor			Thickness of insulation (mm)	Diameter over insulation (Approx.) (mm)	Diameter of armour wire (mm)	Diameter over Armour (Approx.) (mm)	Thickness of outer sheath (mm)	Overall diameter (Approx.) (mm)	Cable weight (Approx.) (kg/km)	Maximum conductor resistance at 20°C (Ω/km)	Minimum insulation resistance at 20°C (MΩ-km)	Ampacities direct burial in ground at 30°C (A)	Allowable ampacities in free air at 40°C (ambient) (A)	Standard length (m/R)
	Nominal cross-sectional area core x mm <sup>2</sup>	Minimum number of wire No./mm	Diameter (Approx.) (mm)												
K3B621010	1 x 10	6	3.72	2.5	10.0	1.25	17.0	1.8	22	580	1.83	3,100	90	100	1,000
K3B621016	1 x 16	6	4.69	2.5	11.0	1.6	18.5	1.8	24	720	1.15	2,800	115	125	1,000
K3B621025	1 x 25	6	5.90	2.5	12.5	1.6	19.5	1.8	25	860	0.727	2,400	150	165	1,000
K3B621035	1 x 35	6	6.95	2.5	13.5	1.6	21.0	1.8	26	990	0.524	2,100	180	200	1,000
K3B621050	1 x 50	6	8.33	2.5	14.5	1.6	22.5	1.8	28	1,180	0.387	1,900	210	240	1,000
K3B621070	1 x 70	12	9.73	2.5	16.5	1.6	24.0	1.8	29	1,420	0.268	1,700	260	295	1,000
K3B621095	1 x 95	15	11.45	2.5	18.0	1.6	25.5	1.9	31	1,730	0.193	1,500	310	365	1,000
K3B621120	1 x 120	18	12.95	2.5	19.5	1.6	27.0	2.0	33	2,030	0.153	1,300	350	420	1,000
K3B621150	1 x 150	18	14.27	2.5	21.0	2.0	29.5	2.0	35	2,440	0.124	1,200	395	475	1,000
K3B621185	1 x 185	30	15.98	2.5	22.5	2.0	31.0	2.1	37	2,850	0.0991	1,100	450	545	500
K3B621240	1 x 240	34	18.47	2.6	25.5	2.0	33.5	2.2	40	3,490	0.0754	1,000	520	640	500
K3B621300	1 x 300	34	20.68	2.8	28.0	2.0	36.5	2.3	43	4,190	0.0601	1,000	585	740	500
K3B621400	1 x 400	53	23.39	3.0	31.5	2.5	41.0	2.4	47	5,450	0.0470	900	670	850	250
K3B621500	1 x 500	53	26.67	3.2	35.5	2.5	44.5	2.6	51	6,620	0.0366	900	760	975	250
K3B621630	1 x 630	53	30.20	3.2	38.5	2.5	48.5	2.7	55	8,080	0.0283	800	860	1,130	250
K3B621800	1 x 800	53	34.00	3.2	42.5	2.5	52.5	2.8	60	9,900	0.0221	700	1,025	1,330	250
K3B6211000	1 x 1,000	53	40.00	3.2	48.5	2.5	58.5	3.1	67	12,190	0.0176	600	1,215	1,520	200

\*\* Depth of laying in ground = 1 m, Rho = 1.2 °C m/watt, Spacing of cable = 2 x cable overall diameter

20 Medium & High Voltage Power Cable


R = Packing in reel



# CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

## CABLE TYPE : CTW-CV-AWA SINGLE CORE CU/XLPE/AWA/PVC 6/10 (12) kV

MEDIUM VOLTAGE CROSS-LINKED POLYETHYLENE INSULATED, COPPER CONDUCTOR WITH ALUMINUM WIRE ARMOUR



### CONSTRUCTION

Conductor	Compact round stranded annealed copper.
Conductor Screen	Semi-conducting cross-linked polyethylene.
Insulation	Cross-linked polyethylene. (XLPE)
Insulation Screen	Semi-conducting cross-linked polyethylene.
Metallic Shield	Annealed copper tape.
Separator Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)
Armour	Aluminum wire.
Separator Tape	Polyester and/or Spunbond tape.
Outer Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)

### APPLICATION

Preferably used for urban networks. Exposed in aerial, direct burial, conduit, open tray and underground duct installation.

### CLASSIFICATION

Maximum Conductor Temperature 90 °C (Normal Operation)  
Maximum Conductor Temperature 250 °C (Short-circuit at 5s maximum duration)

### REFERENCE

IEC 60228 & IEC 60502-2  
\*\* AC Test Voltage : 21 kV

### NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF) Flame retardant sheath can be supplied in accordance with IEC 60332-3.

Product code	Conductor			Thickness of insulation mm	Diameter over insulation (Approx.) mm	Diameter of armour wire mm	Diameter over armour (Approx.) mm	Thickness of outer sheath mm	Overall diameter (Approx.) mm	Cable weight (Approx.) kg/km	Maximum conductor resistance at 20°C Ω/km	Minimum insulation resistance at 20°C MΩ-km	Ampacities direct burial in ground at 30°C A	Allowable ampacities in free air at 40°C (ambient) A	Standard length m/R
	Nominal cross-sectional area core x mm <sup>2</sup>	Minimum number of wire No./mm	Diameter (Approx.) mm												
K3E621016	1 x 16	6	4.69	3.4	13.0	1.6	21.0	1.8	25	810	1.15	3,000	110	120	1,000
K3E621025	1 x 25	6	5.90	3.4	14.0	1.6	22.0	1.8	26	940	0.727	2,700	140	160	1,000
K3E621035	1 x 35	6	6.95	3.4	15.0	1.6	23.0	1.8	27	1,080	0.524	2,400	170	195	1,000
K3E621050	1 x 50	6	8.33	3.4	16.5	1.6	24.5	1.9	29	1,290	0.387	2,200	200	235	1,000
K3E621070	1 x 70	12	9.73	3.4	18.0	1.6	26.0	1.9	30	1,530	0.268	1,900	250	290	1,000
K3E621095	1 x 95	15	11.45	3.4	19.5	1.6	28.0	2.0	32	1,850	0.193	1,700	295	360	1,000
K3E621120	1 x 120	18	12.95	3.4	21.0	2.0	30.0	2.0	35	2,230	0.153	1,600	335	415	1,000
K3E621150	1 x 150	18	14.27	3.4	22.5	2.0	31.5	2.1	36	2,580	0.124	1,500	375	470	1,000
K3E621185	1 x 185	30	15.98	3.4	24.5	2.0	33.0	2.2	38	2,990	0.0991	1,400	430	540	500
K3E621240	1 x 240	34	18.47	3.4	27.0	2.0	36.0	2.2	41	3,610	0.0754	1,200	495	635	500
K3E621300	1 x 300	34	20.68	3.4	29.0	2.0	38.0	2.3	43	4,270	0.0601	1,100	560	735	500
K3E621400	1 x 400	53	23.39	3.4	32.0	2.5	42.0	2.5	48	5,540	0.0470	1,000	640	845	250
K3E621500	1 x 500	53	26.67	3.4	35.5	2.5	46.0	2.6	52	6,650	0.0366	900	725	970	250
K3E621630	1 x 630	53	30.20	3.4	39.0	2.5	49.5	2.7	56	8,130	0.0283	800	820	1,125	250
K3E621800	1 x 800	53	34.00	3.4	43.0	2.5	54.0	2.9	60	9,980	0.0221	700	985	1,325	250
K3E6211000	1 x 1,000	53	40.00	3.4	49.0	2.5	60.0	3.1	67	12,230	0.0176	600	1,185	1,515	200


\*\* Depth of laying in ground = 1 m, Rho = 1.2 °C m/watt, Spacing of cable = 2 x cable overall diameter  
R = Packing in reel



# CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

## CABLE TYPE : CTW-CV-AWA SINGLE CORE CU/XLPE/AWA/PVC 8.7/15 (17.5) kV

MEDIUM VOLTAGE CROSS-LINKED POLYETHYLENE INSULATED, COPPER CONDUCTOR WITH ALUMINUM WIRE ARMOUR



### CONSTRUCTION

Conductor	Compact round stranded annealed copper.
Conductor Screen	Semi-conducting cross-linked polyethylene.
Insulation	Cross-linked polyethylene. (XLPE)
Insulation Screen	Semi-conducting cross-linked polyethylene.
Metallic Shield	Annealed copper tape.
Separator Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)
Armour	Aluminum wire.
Separator Tape	Polyester and/or Spunbond tape.
Outer Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)

### APPLICATION

Preferably used for urban networks. Exposed in aerial, direct burial, conduit, open tray and underground duct installation.

### CLASSIFICATION

Maximum Conductor Temperature 90 °C (Normal Operation)  
Maximum Conductor Temperature 250 °C (Short-circuit at 5s maximum duration)

### REFERENCE

IEC 60228 & IEC 60502-2  
\*\* AC Test Voltage : 30.5 kV

### NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF) Flame retardant sheath can be supplied in accordance with IEC 60332-3.

Product code	Conductor			Thickness of insulation mm	Diameter over insulation (Approx.) mm	Diameter of armour wire mm	Diameter over armour (Approx.) mm	Thickness of outer sheath mm	Overall diameter (Approx.) mm	Cable weight (Approx.) kg/km	Maximum conductor resistance at 20°C Ω/km	Minimum insulation resistance at 20°C MΩ-km	Ampacities direct burial in ground at 30°C A	Allowable ampacities in free air at 40°C (ambient) A	Standard length m/R
	Nominal cross-sectional area core x mm <sup>2</sup>	Minimum number of wire No./mm	Diameter (Approx.) mm												
K3F621025	1 x 25	6	5.90	4.5	16.0	1.6	24.5	1.8	28	1,070	0.727	3,200	140	155	1,000
K3F621035	1 x 35	6	6.95	4.5	17.0	1.6	25.5	1.9	30	1,220	0.524	2,900	170	190	1,000
K3F621050	1 x 50	6	8.33	4.5	18.5	1.6	27.0	1.9	31	1,425	0.387	2,700	200	230	1,000
K3F621070	1 x 70	12	9.73	4.5	20.0	1.6	28.5	2.0	33	1,690	0.268	2,400	250	285	1,000
K3F621095	1 x 95	15	11.45	4.5	22.0	2.0	31.0	2.1	36	2,095	0.193	2,200	295	355	1,000
K3F621120	1 x 120	18	12.95	4.5	23.5	2.0	32.5	2.1	37	2,395	0.153	2,000	335	410	1,000
K3F621150	1 x 150	18	14.27	4.5	25.0	2.0	34.0	2.2	39	2,755	0.124	1,800	375	455	500
K3F621185	1 x 185	30	15.98	4.5	26.5	2.0	36.0	2.2	41	3,160	0.0991	1,700	430	525	500
K3F621240	1 x 240	34	18.47	4.5	29.0	2.0	38.0	2.3	43	3,810	0.0754	1,500	495	620	500
K3F621300	1 x 300	34	20.68	4.5	31.5	2.5	41.0	2.4	47	4,640	0.0601	1,400	560	720	500
K3F621400	1 x 400	53	23.39	4.5	34.5	2.5	45.0	2.5	50	5,755	0.0470	1,300	640	825	250
K3F621500	1 x 500	53	26.67	4.5	38.0	2.5	48.0	2.7	54	6,919	0.0366	1,100	725	950	250
K3F621630	1 x 630	53	30.20	4.5	41.5	2.5	52.0	2.8	58	8,420	0.0283	1,000	820	1,120	250
K3F621800	1 x 800	53	34.00	4.5	45.0	2.5	56.0	2.9	62	10,220	0.0221	900	985	1,305	250
K3F6211000	1 x 1,000	53	40.00	4.5	51.5	2.5	62.0	3.2	69	12,560	0.0176	800	1,185	1,495	200

\*\* Depth of laying in ground = 1 m, Rho = 1.2 °C m/watt, Spacing of cable = 2 x cable overall diameter



# CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

## CABLE TYPE : CTW-CV-AWA SINGLE CORE CU/XLPE/AWA/PVC 12/20 (24) kV

MEDIUM VOLTAGE CROSS-LINKED POLYETHYLENE INSULATED, COPPER CONDUCTOR WITH ALUMINUM WIRE ARMOUR



### CONSTRUCTION

Conductor	Compact round stranded annealed copper.
Conductor Screen	Semi-conducting cross-linked polyethylene.
Insulation	Cross-linked polyethylene. (XLPE)
Insulation Screen	Semi-conducting cross-linked polyethylene.
Metallic Shield	Annealed copper tape.
Separator Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)
Armour	Aluminum wire.
Separator Tape	Polyester and/or Spunbond tape.
Outer Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)

### APPLICATION

Preferably used for urban networks. Exposed in aerial, direct burial, conduit, open tray and underground duct installation.

### CLASSIFICATION

Maximum Conductor Temperature 90 °C (Normal Operation)  
Maximum Conductor Temperature 250 °C (Short-circuit at 5s maximum duration)

### REFERENCE

IEC 60228 & IEC 60502-2  
\*\* AC Test Voltage : 42 kV

### NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF) Flame retardant sheath can be supplied in accordance with IEC 60332-3.

Product code	Conductor			Thickness of insulation (mm)	Diameter over insulation (Approx.) (mm)	Diameter of armour wire (mm)	Diameter over armour (Approx.) (mm)	Thickness of outer sheath (mm)	Overall diameter (Approx.) (mm)	Cable weight (Approx.) (kg/km)	Maximum conductor resistance at 20°C (Ω/km)	Minimum insulation resistance at 20°C (MΩ-km)	Ampacities direct burial in ground at 30°C (A)	Allowable ampacities in free air at 40°C (ambient) (A)	Standard length (m/R)
	Nominal cross-sectional area core x mm <sup>2</sup>	Minimum number of wire No./mm	Diameter (Approx.) (mm)												
K3G621035	1 x 35	6	6.95	5.5	19.5	1.6	27.50	2.0	32	1,360	0.524	3,300	170	200	1,000
K3G621050	1 x 50	6	8.33	5.5	21.0	2.0	29.00	2.0	34	1,645	0.387	3,100	200	240	1,000
K3G621070	1 x 70	12	9.73	5.5	22.5	2.0	31.00	2.1	36	1,925	0.268	2,800	250	295	1,000
K3G621095	1 x 95	15	11.45	5.5	24.0	2.0	33.00	2.1	38	2,240	0.193	2,500	295	365	1,000
K3G621120	1 x 120	18	12.95	5.5	25.5	2.0	34.50	2.2	39	2,560	0.153	2,300	335	420	1,000
K3G621150	1 x 150	18	14.27	5.5	27.0	2.0	36.00	2.2	41	2,905	0.124	2,200	375	475	500
K3G621185	1 x 185	30	15.98	5.5	28.5	2.0	37.50	2.3	43	3,340	0.0991	2,000	430	545	500
K3G621240	1 x 240	34	18.47	5.5	31.0	2.5	41.00	2.4	47	4,150	0.0754	1,800	495	640	500
K3G621300	1 x 300	34	20.68	5.5	33.5	2.5	43.50	2.5	49	4,850	0.0601	1,600	560	740	500
K3G621400	1 x 400	53	23.39	5.5	36.5	2.5	47.00	2.6	53	6,000	0.0470	1,500	640	850	250
K3G621500	1 x 500	53	26.67	5.5	40.0	2.5	50.50	2.7	57	7,130	0.0366	1,300	725	975	250
K3G621630	1 x 630	53	30.20	5.5	43.5	2.5	54.50	2.9	61	8,655	0.0283	1,200	820	1,130	250
K3G621800	1 x 800	53	34.00	5.5	47.5	2.5	58.00	3.0	65	10,510	0.0221	1,100	985	1,330	250
K3G621000	1 x 1,000	53	40.00	5.5	53.5	2.5	64.00	3.2	72	12,820	0.0176	1,000	1,185	1,520	200

\*\* Depth of laying in ground = 1 m, Rho = 1.2 °C m/watt, Spacing of cable = 2 x cable overall diameter  
R = Packing in reel



# CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

## CABLE TYPE : CTW-CV-AWA SINGLE CORE CU/XLPE/AWA/PVC 18/30 (36) kV

MEDIUM VOLTAGE CROSS-LINKED POLYETHYLENE INSULATED, COPPER CONDUCTOR WITH ALUMINUM WIRE ARMOUR



### CONSTRUCTION

Conductor	Compact round stranded annealed copper.
Conductor Screen	Semi-conducting cross-linked polyethylene.
Insulation	Cross-linked polyethylene. (XLPE)
Insulation Screen	Semi-conducting cross-linked polyethylene.
Metallic Shield	Annealed copper tape.
Separator Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)
Armour	Aluminum wire.
Separator Tape	Polyester and/or Spunbond tape.
Outer Sheath	Black Polyvinyl chloride (ST2) ; Optional : Polyethylene (ST7)

### APPLICATION

Preferably used for urban networks. Exposed in aerial, direct burial, conduit, open tray and underground duct installation.

### CLASSIFICATION

Maximum Conductor Temperature 90 °C (Normal Operation)  
Maximum Conductor Temperature 250 °C (Short-circuit at 5s maximum duration)

### REFERENCE

IEC 60228 & IEC 60502-2  
\*\* AC Test Voltage : 63 kV

### NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF) Flame retardant sheath can be supplied in accordance with IEC 60332-3.

Product code	Conductor			Thickness of insulation (mm)	Diameter over insulation (Approx.) (mm)	Diameter of armour wire (mm)	Diameter over armour (Approx.) (mm)	Thickness of outer sheath (mm)	Overall diameter (Approx.) (mm)	Cable weight (Approx.) (kg/km)	Maximum conductor resistance at 20°C (Ω/km)	Minimum insulation resistance at 20°C (MΩ-km)	Ampacities direct burial in ground at 30°C (A)	Allowable ampacities in free air at 40°C (ambient) (A)	Standard length (m/R)
	Nominal cross-sectional area core x mm²	Minimum number of wire No./mm	Diameter (Approx.) (mm)												
K3I621050	1 x 50	6	8.33	8.0	26.0	2.0	34.5	2.2	40	2,030	0.387	4,000	200	235	1,000
K3I621070	1 x 70	12	9.73	8.0	27.5	2.0	36.5	2.3	42	2,320	0.268	3,600	250	290	1,000
K3I621095	1 x 95	15	11.45	8.0	29.0	2.0	38.0	2.3	43	2,660	0.193	3,300	295	360	1,000
K3I621120	1 x 120	18	12.95	8.0	30.5	2.5	40.5	2.4	46	3,160	0.153	3,000	335	415	500
K3I621150	1 x 150	18	14.27	8.0	32.0	2.5	42.5	2.5	48	3,530	0.124	2,800	375	470	500
K3I621185	1 x 185	30	15.98	8.0	34.0	2.5	44.0	2.5	50	3,980	0.0991	2,700	430	540	500
K3I621240	1 x 240	34	18.47	8.0	36.5	2.5	47.0	2.6	53	4,690	0.0754	2,400	495	635	500
K3I621300	1 x 300	34	20.68	8.0	38.5	2.5	49.0	2.7	56	5,400	0.0601	2,200	560	735	250
K3I621400	1 x 400	53	23.39	8.0	41.5	2.5	52.5	2.8	59	6,580	0.0470	2,000	640	845	250
K3I621500	1 x 500	53	26.67	8.0	45.0	2.5	55.5	2.9	63	7,740	0.0366	1,800	725	970	250
K3I621630	1 x 630	53	30.20	8.0	48.5	2.5	59.5	3.1	67	9,320	0.0283	1,600	820	1,125	250
K3I621800	1 x 800	53	34.00	8.0	52.5	2.5	63.5	3.2	71	11,220	0.0221	1,500	985	1,325	250
K3I6211000	1 x 1,000	53	40.00	8.0	58.5	3.15	71.5	3.5	80	13,920	0.0176	1,400	1,185	1,515	200

\*\* Depth of laying in ground = 1 m, Rho = 1.2 °C m/watt, Spacing of cable = 2 x cable overall diameter