



CABLE TYPE : **CTW-CV-CWS SINGLE CORE CU/XLPE/CWS/PE 69 kV**

HIGH VOLTAGE CROSS-LINKED POLYETHYLENE CABLE, COPPER CONDUCTOR WITH COPPER WIRE SHIELD



APPLICATION

CLASSIFICATION

Conductor	Compact round stranded annealed copper.	Preferably used for urban networks. Suitable For use in duct, trays and direct burial in ground, subjected to immerse in water all the time.	Maximum Conductor Temperature 90 °C (Normal Operation)
Conductor Screen	Semi-conducting tape with extruded. semi-conducting cross-linked polyethylene.		Maximum Conductor Temperature 250 °C (Short-circuit at 5s maximum duration)
Insulation	Cross-linked polyethylene. (XLPE)		
Insulation Screen	Semi-conducting cross-linked polyethylene.		
Synthetic water blocking layer	Semi-conductive water blocking tape.	R E F E R E N C E IEC 60228 & IEC 60840 ** AC Test Voltage : 90 kV	N O T E A special FR-PVC or Low Smoke Halogen Free (LSHF) Flame retardant sheath can be supplied in accordance with IEC 60332-3.
Metallic Shield	Annealed copper wire with copper contact tape.		
Synthetic water blocking layer	Non-conductive water blocking tape.		
Radial water barrier	Plastic-coated Aluminum tape.		
Outer Sheath	Black polyethylene (ST7) ; (Optional : with rib)		

[illegible]

** Depth of laying in ground = 1 m, Rho = 1.2 °C m/watt, Spacing of cable = 2 x cable overall diameter
R = Packing in reel