




CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

CABLE TYPE : CTW-CV-FRPVC SINGLE CORE CU/XLPE/FRPVC 0.6/1(1.2) kV

LOW VOLTAGE CROSS-LINKED POLYETHYLENE POWER CABLE COPPER CONDUCTOR WITHOUT ARMOUR

PAGE 1 / 2



CONSTRUCTION

- Conductor** Compact or Round concentric lay stranded copper
- CR : Concentric lay stranded of conductor : ≤ 10 sq.mm.
- CP : Compact round concentric lay stranded of conductor : > 10 sq.mm.
- Insulation** Cross-linked polyethylene (XLPE)
Colour : Natural
- Sheath** Flame retardant polyvinyl chloride (FRPVC:ST2)
Optional : Polyethylene (PE:ST7)
Colour : Black

APPLICATION

Preferably used for installation exposed or in raceway wet or dry location or direct burial in ground.

CLASSIFICATION

Maximum conductor temperature 90°C
Circuit voltage does not exceed 1,000 volts.

REFERENCE

⚡ TIS 2143
IEC 60228, IEC 60502-1
AC Test Voltage : 3.5 kV


NOTE

. special FR-PVC or Low Smoke Halogen Free (LSHF)* Flame Retardant Sheath can be supplied in accordance with IEC 60332-3,
*For LSHF : IEC 60754, IEC 61034

CTW-CV		Conductor			Thickness of Insulation	Thickness of Sheath	Overall Diameter (Approx.)	Cable Weight (Approx.)	Maximum Conductor Resistance at 20°C	Minimum Insulation Resistance at 90°C	Standard Packing
PRODUCT CODE	SIZE sq.mm.	Nominal Cross-Sectional Area sq.mm.	Number of Wire No.	Diameter (Approx.) mm							
C76014501	1 x 1.5	1.5	7:CR	1.56	0.7	1.4	7.5	55	12.10	1.1098	1,000/R
C76014502	1 x 2.5	2.5	7:CR	2.01	0.7	1.4	8.0	70	7.41	0.9229	1,000/R
C76014004	1 x 4	4	7:CR	2.52	0.7	1.4	8.5	90	4.61	0.7762	1,000/R
C76014006	1 x 6	6	7:CR	3.09	0.7	1.4	9.0	115	3.08	0.6598	1,000/R
C76014010	1 x 10	10	7:CR	3.99	0.7	1.4	10.0	160	1.83	0.5340	1,000/R
C76018016	1 x 16	16	7:CP	4.69	0.7	1.4	10.5	215	1.15	0.4636	1,000/R
C76018025	1 x 25	25	7:CP	5.90	0.9	1.4	12.0	315	0.727	0.4612	1,000/R
C76018035	1 x 35	35	7:CP	6.95	0.9	1.4	13.5	420	0.524	0.3996	1,000/R
C76018050	1 x 50	50	19:CP	8.33	1.0	1.4	15.0	575	0.387	0.3704	1,000/R
C76018070	1 x 70	70	19:CP	9.73	1.1	1.4	16.5	775	0.268	0.3482	1,000/R
C76018095	1 x 95	95	19:CP	11.45	1.1	1.5	18.5	1,025	0.193	0.3007	1,000/R
C76018120	1 x 120	120	19:CP	12.95	1.2	1.5	20.0	1,275	0.153	0.2890	1,000/R
C76018150	1 x 150	150	37:CP	14.27	1.4	1.6	22.0	1,585	0.124	0.3014	1,000/R
C76018185	1 x 185	185	37:CP	15.98	1.6	1.6	24.5	1,940	0.0991	0.3047	1,000/R
C76018240	1 x 240	240	37:CP	18.47	1.7	1.7	27.5	2,495	0.0754	0.2813	1,000/R
C76018300	1 x 300	300	61:CP	20.68	1.8	1.8	30.0	3,090	0.0601	0.2664	500/R

C = Packing in coil
R = Packing in reel

Building Wire & Low Voltage Power Cable



CONSTRUCTION

Conductor

Compact or Round concentric lay stranded copper

- CR : Concentric lay stranded of conductor : ≤ 10 sq.mm.
- CP : Compact round concentric lay stranded of conductor : > 10 sq.mm.

Insulation

Cross-linked polyethylene (XLPE)
Colour : Natural

Sheath

Flame retardant polyvinyl chloride (FRPVC:ST2)
Optional : Polyethylene (PE:ST7)
Colour : Black

APPLICATION

Preferably used for installation exposed or in raceway wet or dry location or direct burial in ground.

REFERENCE

 TIS 2143
IEC 60228, IEC 60502-1
AC Test Voltage : 3.5 kV

CLASSIFICATION

Maximum conductor temperature 90°C
Circuit voltage does not exceed 1,000 volts.

NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF)* Flame Retardant Sheath can be supplied in accordance with IEC 60332-3,
*For LSHF : IEC 60754, IEC 61034


[illegible]



CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

CABLE TYPE : CTW-CV-FRPVC TWO CORES CU/XLPE/FRPVC 0.6/1(1.2) kV

LOW VOLTAGE CROSS-LINKED POLYETHYLENE POWER CABLE COPPER CONDUCTOR WITHOUT ARMOUR



CONSTRUCTION

Conductor	Compact or Round concentric lay stranded copper - CR : Concentric lay stranded of conductor : ≤ 10 sq.mm. - CP : Compact round concentric lay stranded of conductor : > 10 sq.mm.
Insulation	Cross-linked polyethylene (XLPE) Colour : Blue, Brown
Filler	PVC/PE Rod or Polypropylene (Nonhygroscopic material)
Wrapping Tape	Polyester (Mylar) and / or Spunboun tape
Sheath	Flame retardant polyvinyl chloride (FRPVC:ST2) Optional : Polyethylene (PE:ST7) Colour : Black

APPLICATION

Preferably used for installation exposed or in raceway wet or dry location or direct burial in ground.

REFERENCE

⚡ TIS 2143
IEC 60228, IEC 60502-1
AC Test Voltage : 3.5 kV

CLASSIFICATION

Maximum conductor temperature 90°C
Circuit voltage does not exceed 1,000 volts.

NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF)* Flame Retardant Sheath can be supplied in accordance with IEC 60332-3,
*For LSHF : IEC 60754, IEC 61034

CTW-CV		Conductor			Thickness of Insulation	Thickness of Sheath	Overall Diameter (Approx.)	Cable Weight (Approx.)	Maximum Conductor Resistance at 20°C	Minimum Insulation Resistance at 90°C	Standard Packing
PRODUCT CODE	SIZE sq.mm.	Nominal Cross-Sectional Area sq.mm.	Number of Wire No.	Diameter (Approx.) mm							
C76024501	2 x 1.5	1.5	7:CR	1.56	0.7	1.8	11.5	145	12.1	1.1098	1,000/R
C76024502	2 x 2.5	2.5	7:CR	2.01	0.7	1.8	12.5	180	7.41	0.9229	1,000/R
C76024004	2 x 4	4	7:CR	2.52	0.7	1.8	13.5	230	4.61	0.7762	1,000/R
C76024006	2 x 6	6	7:CR	3.09	0.7	1.8	14.5	295	3.08	0.6598	1,000/R
C76024010	2 x 10	10	7:CR	3.99	0.7	1.8	17.0	380	1.83	0.5340	1,000/R
C76028016	2 x 16	16	7:CP	4.69	0.7	1.8	18.5	505	1.15	0.4636	1,000/R
C76028025	2 x 25	25	7:CP	5.90	0.9	1.8	21.5	745	0.727	0.4612	1,000/R
C76028035	2 x 35	35	7:CP	6.95	0.9	1.8	24.0	975	0.524	0.3996	1,000/R
C76028050	2 x 50	50	19:CP	8.33	1.0	1.8	27.0	1,330	0.387	0.3704	1,000/R
C76028070	2 x 70	70	19:CP	9.73	1.1	1.8	30.5	1,785	0.268	0.3482	1,000/R
C76028095	2 x 95	95	19:CP	11.45	1.1	1.9	34.5	2,355	0.193	0.3007	1,000/R
C76028120	2 x 120	120	19:CP	12.95	1.2	2.0	38.0	2,945	0.153	0.2890	1,000/R
C76028150	2 x 150	150	37:CP	14.27	1.4	2.2	42.5	3,665	0.124	0.3014	500/R
C76028185	2 x 185	185	37:CP	15.98	1.6	2.3	47.0	4,500	0.0991	0.3047	500/R
C76028240	2 x 240	240	37:CP	18.47	1.7	2.5	53.0	5,785	0.0754	0.2813	250/R
C76028300	2 x 300	300	61:CP	20.68	1.8	2.6	58.5	7,145	0.0601	0.2664	250/R
C76028400	2 x 400	400	61:CP	23.39	2.0	2.9	65.5	9,405	0.0470	0.2609	250/R

C = Packing in coil
R = Packing in reel


Building Wire & Low Voltage Power Cable



CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

CABLE TYPE : CTW-CV-FRPVC THREE CORES CU/XLPE/FRPVC 0.6/1(1.2) kV

LOW VOLTAGE CROSS-LINKED POLYETHYLENE POWER CABLE COPPER CONDUCTOR WITHOUT ARMOUR



CONSTRUCTION

Conductor	Compact or Round concentric lay stranded copper - CR : Concentric lay stranded of conductor : ≤ 10 sq.mm. - CP : Compact round concentric lay stranded of conductor : > 10 sq.mm.
Insulation	Cross-linked polyethylene (XLPE) Colour : Blue, Brown
Filler	PVC/PE Rod or Polypropylene (Nonhygroscopic material)
Wrapping Tape	Polyester (Mylar) and / or Spunbond tape
Sheath	Flame retardant polyvinyl chloride (FRPVC:ST2) Optional : Polyethylene (PE:ST7) Colour B=ack

APPLICATION

Preferably used for installation exposed or in raceway wet or dry location or direct burial in ground.

REFERENCE

⚡ TIS 2143
IEC 60228, IEC 60502-1
AC Test Voltage : 3.5 kV

CLASSIFICATION

Maximum conductor temperature 90°C
Circuit voltage does not exceed 1,000 volts.

NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF)* Flame Retardant Sheath can be supplied in accordance with IEC 60332-3,
*For LSHF : IEC 60754, IEC 61034


CTW-CV		Conductor			Thickness of Insulation	Thickness of Sheath	Overall Diameter (Approx.)	Cable Weight (Approx.)	Maximum Conductor Resistance at 20°C	Minimum Insulation Resistance at 90°C	Standard Packing
		Nominal Cross-Sectional Area	Number of Wire	Diameter (Approx.)							
PRODUCT CODE	SIZE sq.mm.	sq.mm.	No./mm	mm	mm	mm	mm	kg/km	Ω/km	MΩ-km	m
C76034501	3 x 1.5	1.5	7:CR	1.56	0.7	1.8	12.0	165	12.1	1.1098	1,000/R
C76034502	3 x 2.5	2.5	7:CR	2.01	0.7	1.8	13.0	210	7.41	0.9229	1,000/R
C76034004	3 x 4	4	7:CR	2.52	0.7	1.8	14.0	275	4.61	0.7762	1,000/R
C76034006	3 x 6	6	7:CR	3.09	0.7	1.8	15.5	360	3.08	0.6598	1,000/R
C76034010	3 x 10	10	7:CR	3.99	0.7	1.8	18.0	495	1.83	0.5340	1,000/R
C76038016	3 x 16	16	7:CP	4.69	0.7	1.8	19.5	670	1.15	0.4636	1,000/R
C76038025	3 x 25	25	7:CP	5.90	0.9	1.8	23.0	995	0.727	0.4612	1,000/R
C76038035	3 x 35	35	7:CP	6.95	0.9	1.8	25.5	1,320	0.524	0.3996	1,000/R
C76038050	3 x 50	50	19:CP	8.33	1.0	1.8	29.0	1,820	0.387	0.3704	1,000/R
C76038070	3 x 70	70	19:CP	9.73	1.1	1.9	33.0	2,480	0.268	0.3482	1,000/R
C76038095	3 x 95	95	19:CP	11.45	1.1	2.0	37.0	3,285	0.193	0.3007	500/R
C76038120	3 x 120	120	19:CP	12.95	1.2	2.1	41.0	4,110	0.153	0.2890	500/R
C76038150	3 x 150	150	37:CP	14.27	1.4	2.3	45.5	5,120	0.124	0.3014	500/R
C76038185	3 x 185	185	37:CP	15.98	1.6	2.4	50.5	6,300	0.0991	0.3047	500/R
C76038240	3 x 240	240	37:CP	18.47	1.7	2.6	57.0	8,100	0.0754	0.2813	250/R
C76038300	3 x 300	300	61:CP	20.68	1.8	2.7	62.5	10,025	0.0601	0.2664	250/R
C76038400	3 x 400	400	61:CP	23.39	2.0	3.0	70.5	13,220	0.0470	0.2609	250/R



CHAROONG THAI WIRE & CABLE PUBLIC COMPANY LIMITED

CABLE TYPE : CTW-CV-FRPVC FOUR CORES CU/XLPE/FRPVC 0.6/1(1.2) kV

LOW VOLTAGE CROSS-LINKED POLYETHYLENE POWER CABLE COPPER CONDUCTOR WITHOUT ARMOUR



CONSTRUCTION

Conductor	Compact or Round concentric lay stranded copper - CR : Concentric lay stranded of conductor : ≤ 10 sq.mm. - CP : Compact round concentric lay stranded of conductor : > 10 sq.mm.
Insulation	Cross-linked polyethylene (XLPE) Colour : Blue, Brown
Filler	PVC/PE Rod or Polypropylene (Nonhygroscopic material)
Wrapping Tape	Polyester (Mylar) and / or Spunboun tape
Sheath	Flame retardant polyvinyl chloride (FRPVC:ST2) Optional : Polyethylene (PE:ST7) Colour Black

APPLICATION

Preferably used for installation exposed or in raceway wet or dry location or direct burial in ground.

REFERENCE

⚡ TIS 2143
IEC 60228, IEC 60502-1
AC Test Voltage : 3.5 kV

CLASSIFICATION

Maximum conductor temperature 90°C
Circuit voltage does not exceed 1,000 volts.

NOTE

A special FR-PVC or Low Smoke Halogen Free (LSHF)* Flame Retardant Sheath can be supplied in accordance with IEC 60332-3,
*For LSHF : IEC 60754, IEC 61034

CTW-CV		Conductor			Thickness of Insulation	Thickness of Sheath	Overall Diameter (Approx.)	Cable Weight (Approx.)	Maximum Conductor Resistance at 20°C	Minimum Insulation Resistance at 90°C	Standard Packing
		Nominal Cross-Sectional Area	Number of Wire	Diameter (Approx.)							
PRODUCT CODE	SIZE sq.mm.	sq.mm.	No.	mm	mm	mm	mm	kg/km	Ω /km	M Ω -km	m
C76044501	4 x 1.5	1.5	7:CR	1.56	0.7	1.8	13.0	195	12.1	1.1098	1,000/R
C76044502	4 x 2.5	2.5	7:CR	2.01	0.7	1.8	14.0	250	7.41	0.9229	1,000/R
C76044004	4 x 4	4	7:CR	2.52	0.7	1.8	15.0	335	4.61	0.7762	1,000/R
C76044006	4 x 6	6	7:CR	3.09	0.7	1.8	16.5	435	3.08	0.6598	1,000/R
C76044010	4 x 10	10	7:CR	3.99	0.7	1.8	19.5	610	1.83	0.5340	1,000/R
C76048016	4 x 16	16	7:CP	4.69	0.7	1.8	21.0	860	1.15	0.4636	1,000/R
C76048025	4 x 25	25	7:CP	5.90	0.9	1.8	25.0	1,285	0.727	0.4612	1,000/R
C76048035	4 x 35	35	7:CP	6.95	0.9	1.8	28.0	1,715	0.524	0.3996	1,000/R
C76048050	4 x 50	50	19:CP	8.33	1.0	1.8	32.0	2,365	0.387	0.3704	1,000/R
C76048070	4 x 70	70	19:CP	9.73	1.1	2.0	36.5	3,255	0.268	0.3482	500/R
C76048095	4 x 95	95	19:CP	11.45	1.1	2.1	41.0	4,315	0.193	0.3007	500/R
C76048120	4 x 120	120	19:CP	12.95	1.2	2.3	45.5	5,430	0.153	0.2890	500/R
C76048150	4 x 150	150	37:CP	14.27	1.4	2.4	50.5	6,740	0.124	0.3014	250/R
C76048185	4 x 185	185	37:CP	15.98	1.6	2.6	56.0	8,310	0.0991	0.3047	250/R
C76048240	4 x 240	240	37:CP	18.47	1.7	2.8	63.5	10,700	0.0754	0.2813	250/R
C76048300	4 x 300	300	61:CP	20.68	1.8	3.0	70.0	13,275	0.0601	0.2664	200/R
C76048400	4 x 400	400	61:CP	23.39	2.0	3.3	78.5	17,515	0.0470	0.2609	150/R

C = Packing in coil
R = Packing in reel

Building Wire & Low Voltage Power Cable